

Promat



Technical Data Sheet

BLANKET

DALFRATHERM[®]-1260 HYBRID

DALFRATHERM®-1260 HYBRID blankets are part of an extensive range of high temperature insulation blankets targeted on achieving the highest possible thermal insulation value and handling strength.

DALFRATHERM®-1260 HYBRID is the new standard for a classical RCF blanket. It is not the standard Kaolin based blanket, neither it is the standard Alumina/Silica fibre; it is the best of both worlds.

Typical applications

- Thermal insulation for furnace lining
- Thermal insulation for lining stacks and chimneys
- Blanket for module making
- Furnace lining in Ceramics and Glass
- Thermal insulation for Petrochemical Industry
- Thermal insulation for Steel Treatment
- General technical insulation of furnaces and technical installations

Benefits

- Proven technical solution
- Low shot technology
- Excellent insulation performance
- High handling strength
- Unaffected by most chemicals
- Excellent thermal stability
- Resistant to thermal shock

DALFRATHERM®-1260 HYBRID blankets share the Ultra Low Shot technology with the DALFRATHERM®-1200 ULS blankets, providing high handling strength, exceptional thermal insulating performance and reversible flexibility after compression.

DALFRATHERM®-1260 HYBRID blankets are available in a wide range of dimensions and densities. All products have been developed to meet requirements specific for the final application.

Sustainability

Our world has changed in the past few decades with reduced CO2 emissions and energy consumption as the key drivers. Therefore focus must be on the most effective methods of saving energy.

A high performance insulation lining for the technical installation not only saves energy but also provides energy bill savings, avoids heat loss and demands less power.

Type

Blanket from high temperature Refractory Ceramic Fiber insulation wool.

Temperature range

DALFRATHERM®-1260 HYBRID blankets have a classification temperature of 1260°C and are recommended for continuous use up to 1100°C in clean oxidizing atmospheres.



Grade			RCF	
Colour			white	
Classification temperature		°C (°F)	1260°C (2300°F)	
Continuous use temperature		°C (°F)	1100°C (2012°F)	
Density	EN 1094-4	kg/m ³	96	128
Tensile strength	GB/T 17911	kPa	80	100
Linear shrinkage	GB/T 17911	%	< 3	
12h@1100°C (2012°F)				
12h@1200°C (2192°F)				
12h@1400°C (2552°F)				
Thermal conductivity	ASTM C201	W/m.K		
200°C (392°F)			0,06	0,05
400°C (752°F)			0,10	0,09
600°C (1112°F)			0,15	0,13
800°C (1472°F)			0,21	0,18
1000° (1832°F)			0,29	0,25
1200° (2192°F)			-	-
Chemical composition	GB/T 21114	%		
SiO ₂			53 - 55	
Al ₂ O ₃			44 - 46	
Fe ₂ O ₃			< 0,6	
Others			< 0,4	

Availability (X = standard; O = on special demand)

Thickness mm (inch)	64	96	128	160	L mm (inch)	W mm (inch)
6 (0,24)		O	X		5500 (216,54)	610 (24,02)
13 (0,51)	O	X	X		14640 (576,38)	610 (24,02)
19 (0,75)	O	O	O		9760 (384,25)	610 (24,02)
25 (0,98)	O	X	X		7320 (288,19)	610 (24,02)
38 (1,5)	O	X	X		4880 (192,13)	610 (24,02)
50 (1,97)	O	X	X		3660 (144,09)	610 (24,02)

Promat

Etex Building Performance NV

Bormstraat 24
2830 Tiselt
Belgium
+32 2 778 12 11
industry@promat.com
www.promat.com/en/industry

Etex Building Performance GmbH

Scheifenkamp 16
40878 Ratingen
Germany
+49 2102 493 0
industry.verkauf@promat.de
www.promat.com/de/industry

Promat SpA

Via Provinciale 10
24040 Filago BG
Italy
+39 0350069500
industryITA@promat.com
www.promat.com/it-it/industry

Etex France Building Performance S.A.S

500 rue Marcel Demonque, Pôle Agroparc
84915 Avignon Cedex 9
France
+33 (0)4 32 44 44 90
industryFR@promat.com
www.promat.com/fr-fr/industry

Promat Iberica, S.A.

Calle Velázquez 47, 6° izquierda
28001 Madrid
Spain
+34 917 811 550
info@promat.es
www.promat.com/en/industry

Promat TOP Sp. z o.o.

ul.Przeclawska 8
03-879 Warszawa
Poland
+48 22 212 22 95
ei.pl@etexgroup.com
www.promat.com/pl-pl/industry

Promat s.r.o.

V. P. Čkalova 784/22
160 00 Praha 6 - Bubeneč
Czech Republic
+420 224 390 811
pavel.dvorak@etexgroup.com
www.promat.com/cs-cz/industry

Eternit Baltic

J. Dalinkevičiaus str. 2H
Naujoji Akmenė 85118
Lithuania
+370 42 55 68 49
industry@promat.com
www.promat.com/en/industry

Etex Sverige

Hästvägen 4A
212 35 Malmö
Sweden
+44 (0)800 588 4444
industryuk@promat.co.uk
www.promat.com/en-gb/inds

Promat UK Limited

B1 The Innovation Centre
Pilsworth Road - Heywood Distribution Park
Heywood Lancashire OL10 2TS
United Kingdom
+44 (0)800 588 4444
industryuk@promat.co.uk
www.promat.com/en-gb/inds

Promat Inc.

1731 Fred Lawson Drive
Maryville, TN 37801
USA
+1 888 681 0155
industryUS@promat.com
www.promat.com/en-us/industry

Marley Building Systems

2 Setchell Rd
Roodekop
Germiston 1401
South Africa
+27 (0)11 389 4500,
industry@promat.com
www.promat.com/en/industry

Promat Fire Protection LLC

Plot # 597 - 921 - Dubai Investment Park 2
Dubai
United Arab Emirates
+971 4 885 3070

Promat Japan Corporation

Hulic Kakigaracho Bldg., 1-28-5
Nihonbashi Kakigara-cho, Chuo-ku,
Tokyo 103-0014
Japan
+81-3-3808-2820
sales@promat.jp
www.promat.com/ja-jp/industry

Promat Malaysia

Sdn. Bhd. ,Unit 19-02-01, Level 2,
Wisma Tune, No 19, Lorong Dungun, Damansara
Heights
50490 Kuala Lumpur
Malaysia
+603 2095 8555 ext. 140
www.promat.com/en/industry

Promat International Ltd (Korea Branch)

11F, 117, Namdaemun-ro
Jung-gu, Seoul, 04522
South Korea
+82 70 7794 8216
www.promat.com/en/industry

Promat Fire & Insulation Private Ltd

Global Business Park Unit No. 605, 6th Floor, Tower B,
Mehrauli Gurgaon Road, Sector 26, Gurgaon,
122 002 Haryana
India
+91-124-434-6865
promatindia@etexgroup.com
www.promat.com/en/industry

All data contained in this publication are provided in good faith and are correct at the time of printing. Data are typical values, are representative of production and are subject to normal production fluctuations, they should not be deemed to constitute or imply any warranty of performance, the user is held responsible for determining the suitability of the products for the given application. Errors and omissions excepted. Promat accepts no legal responsibility for use or reliance upon this data. All drawings and representations remain our exclusive property and cannot be used, totally or in part, without our prior written approval. Excerpts, reproductions, copies, etc. of our publications require our prior approval. This publication renders all previous ones invalid. Our terms of delivery and payment apply in the event of any claim. Promat and Microtherm are registered trademarks.

© Copyright Etex NV, Brussels, Belgium.

All rights reserved. 2020-06

Etex Industry c/o Microtherm N.V.
Industriepark-Noord 1
9100 Sint-Niklaas
Belgium
+32 (0)3 760 19 80
info@promat-industry.com
www.promat-industry.com

